

PRODUCT DATA SHEET

PEB 722

Tyre Construction: Bias

Type: Tube Less

Main Applications: Reach Stacker

TRA Code: IND 4.5 (Deep Tread)



Salient Features:

Strong Casing with Sturdy Tread Design:

Used in Heavy duty applications.

High Rubber Mass at Tread Centre:

Higher traction and better load-carrying capacity.

Specially Formulated Tread Compound:

Quick heat dissipation and cooler running and longer service life on concrete surfaces.

Reinforced Bead Bundle:

Minimizes chances of bead failure.

Extra Deep Tread with Higher Base Cover:

Higher Mileage.



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	PR & LI/SI	Inflation Pressure	Recommend load (kg) (lbs)	
		SW	OD					Speed (kmph) (mph)	
		mm	mm				mm	mm	Bar
18.00-25	13.00/2.5	inch	inch	inch	inch	psi	6	16	
		528	1675	747	5010	10.3	22950	21250	
		20.8	65.9	29.4	197.2	150	50600	46860	

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ **E:** enquiry@ascensotyres.com ■ **W:** www.ascensotyres.com